



# FINGERPUNCH



Model #AT-FP

Almex Choice™ FingerPunch punches both ends of the belt at the same time, eliminating waste. This fully automatic and pneumatic machine makes finger punching quick and easy. It is suitable for prepping finger and finger-over-finger splices for PVC and polyurethane belts up to 8mm thick and 3m wide.

### FEATURES:

- Sturdy subframe
- Automated 8" cylinder, steel punching head for straight and angled configurations
- Punching board
- High-speed steel blades
- Two pneumatic cylinder clamps to hold belt in place
- Control panel
- Up to 100 psi air supply
- Unattended operation during punching operation
- Castors for ultimate portability

## SPECIFICATIONS

### 2M FINGERPUNCH

WIDTH	LENGTH	VOLTAGE	WEIGHT	MAX WIDTH	SPEED	MAX LOAD	MAX THICKNESS	MIN LENGTH
2.5 M	1 M	220 1PH	400 KG	2 M	800 MM/MIN	N/A	8 MM	N/A

### 3M FINGERPUNCH

WIDTH	LENGTH	VOLTAGE	WEIGHT	MAX WIDTH	SPEED	MAX LOAD	MAX THICKNESS	MIN LENGTH
3.5 M	1 M	220 1PH	750 KG	2 M	800 MM/MIN	N/A	8 MM	N/A



**Note:** The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011