



# PVC COLD BOND CEMENT & HARDENER



Photo shows 800 ml / .25 gal cement with 35 gr / 1.2 oz hardener.

PVC is the ideal cement for splicing PVC belting, bonding PVC cleats and v-guides to belting. It is also excellent for bonding PVC sheet to PVC sheet.

## FEATURES

- Excellent moisture and oil resistance
- Good flexibility
- PVC is an M.E.K. based cement, and is available in four different sizes
- Use only with Fusion Systems PVC hardener
- Strong initial bond strength, allows quick 4 - 6 hour turnaround time
- Recommended for PVC, urethane and most synthetic bonding
- NOTE: Do not use Fusion Clean as a solvent with PVC, use only M.E.K.

## PVC HARDENER

PRODUCT CODE	GRAM	OUNCE
CC-PVC-018	18	.63
CC-PVC-035	35	1.2

## PVC COLD BOND CEMENT

PRODUCT CODE	VOLUME		WEIGHT		COVERAGE		HARDENER BOTTLE QUANTITY
	LITER	GAL	KG	LBS	M <sup>2</sup>	FT <sup>2</sup>	
CC-PVC-001	.4	.12	.3	.7	1.4	15	1 CH-PVC-018
CC-PVC-002	.8	.25	.6	1.3	2.8	30	1 CH-PVC-035
CC-PVC-010	4	1	3	6.6	14	150	5 CH-PVC-035
CC-PVC-200	200	50	173	381	695	7500	250 CH-PVC-035

PVC PROPERTIES	
Colour	Clear (Amber)
Pot Life	4 Hours @ 21 °C / 70 °F
Working Temperature	-40 °C to 79 °C / -40 °F to 175 °F
Shelf Life	24 months in a cool, dark location



**Note:** The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.