


MSHA CS-21 FABRIC BELT COVER STOCK



Almex 48601 MSHA Grade Fabric Belt Cover Stock is an uncured rubber for hot vulcanized belt splicing. It is designed for use as a cover rubber replacement material in splicing MSHA Grade fabric conveyor belts. The material is designed to be used in both finger and step splices of MSHA Grade fabric conveyor belts.

FEATURES

- Enhances working life of MSHA Grade fabric belt splices
- Improves flexibly and strength of MSHA Grade conveyor belt splices
- Eliminates surface contamination (normal application) with double sided poly
- Uses poly colour coding to ID compound

MSHA CS-21 FABRIC BELT COVER STOCK

	POLY COLOR	THICKNESS/GAUGE			WIDTH		LENGTH		ROLL WEIGHT	
PRODUCT CODE	BOTH SIDES	FRAC	ММ	IN	М	IN	М	FT	KG	LB
AA-FBCMSHA-062	Purple	1/16	1.6	.062	.5	20	15	50	13.9	30.6
AA-FBCMSHA-125	Purple	1/8	3.2	.125	.5	20	8	25	14.8	32.7
AA-FBCMSHA-187	Purple	3/16	4.7	.187	.5	20	5	15	13.6	30.0

MSHA CS-21 FABRIC BELT COVER STOCK PROPERTIES					
Base Polymer	SBR/BR Rubber				
Rubber Color	Black				
Poly Liner Color	Purple (double sided)				
Specific Gravity	1.38 - 1.42				
Hardness	69 - 78 Shore A				
Rubber Tensile	2200 - 2400 psi				
Rubber Elongation	400 - 600% (at break)				
Shelf Life	6 Months at 70 °F (21 °C) or 12 Months at 50 °F (10 °C)				



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.