

# SA 2000+

## COLD BOND CEMENT & HARDENER

**SA 2000+** is designed to be a fast-curing cement that will let you return a lagged pulley to service safely. It is ideal for bonding rubber to steel, rubber to rubber, rubber to fabric and fabric to fabric. It will also bond wood, fiberglass, concrete and urethane.

### FEATURES:

SA 2000+ is a chloroprene-based cement.

- Non-flammable
- High initial and permanent adhesion
- Mixed in 9 Almex locations globally for freshness and quick shipment



#### Cement Properties:

Colour: Black  
 Pot Life: 3 Hours @ 21 °C (70 °F)  
 Working Temperature: -40 °C to 82 °C (-40 °F to 180 °F)  
 Calculated Coverage:  
 1 kg: 2.8 M<sup>2</sup> (30 ft<sup>2</sup>)  
 5 kg: 14 M<sup>2</sup> (150 ft<sup>2</sup>)  
 290 kg: 697 M<sup>2</sup> (7500 ft<sup>2</sup>)  
 Shelf Life: 24 months in a cool, dark location.

#### Hardener Properties:

Colour: Clear  
 Calculated Coverage:  
 1 bottle per 1 kg (2.2 Lbs.)  
 5 per 5 kg (11 Lbs.)  
 290 per 290 kg (640 Lbs.)  
 Shelf Life: 24 months in a cool, dark location.

SA 2000+ CEMENT PRODUCT CODE	WEIGHT ( METRIC / IMPERIAL )
CC-SA2000+-002	1 kg / 2.2 Lbs.
CC-SA2000+-010	5 kg / 11 Lbs.
CC-SA2000+-200	290 kg / 640 Lbs.

SA 2000+ CEMENT PRODUCT CODE	WEIGHT ( METRIC / IMPERIAL )
CH-SA2000+-035	35 gr / 1.2 oz