

SA 4000+ COLD BOND CEMENT & HARDENER



SA 4000+ is designed to be a fast-curing cement for returning a lagged pulley to service safely. It is ideal for bonding rubber to steel, rubber to rubber, rubber to fabric and fabric to fabric. It will also bond wood, fiberglass, concrete and urethane.

FEATURES:

- SA 4000+ is an ethyl acetate-based chloroprene cement
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Mixed in Almex locations globally for freshness and quick shipment
- Flammable



Cement Properties:

Colour: Dark Grey

Flammable

Pot Life: 2-3 Hours @ 21 °C (70 °F)

Working Temperature: -40 °C to 82 °C (-40 °F to 180 °F)

Calculated Coverage:

660 gr: 2.8 M² (30 ft²)

3.3 kg: 14 M² (150 ft²)

175 kg: 697 M² (7500 ft²)

Shelf Life: 24 months in a cool dark location.

Hardener Properties:

Colour: Amber-tinted Clear

Calculated Coverage:

1 bottle per 660 gr (1.5 Lbs.)

5 per 3.3 kg (7.7 Lbs.)

250 per 175 kg (386 Lbs.)

Shelf Life: 24 months in a cool dark location.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CC-SA4000+-002	660 gr / 1.5 Lbs.
CC-SA4000+-010	3.3 kg / 7.5 Lbs.
CC-SA4000+-200	175 kg / 386 Lbs.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CH-SA4000+-035	35 gr / 1.2 oz

KIT PRODUCT CODE	DESCRIPTION	WEIGHT (METRIC/IMPERIAL)
CC-SA4000+-002KIT	Cold Bond Cement (660 gr / 1.5 Lbs.) & Hardener (35 gr / 1.2 oz)	1.1 kg / 2.3 Lbs.

NA

Shaw Almex
Europe B.V.
☎ 31 646648648

Shaw Almex
Industries, Canada
☎ 1 905 643 7750

Shaw Almex
Industries, Canada
☎ 1 705 746 5884

Shaw Almex
Fusion, LLC, U.S.A.
☎ 1 404 292 8600

Shaw Almex
Africa (Pty) Ltd.
☎ 27 11 794 8262

ALMEX
GROUP
www.almex.com 1.800.977.5423