





The **Almexpad Senior 3.0** is a ruggedized, 10" touch screen Android tablet. It interfaces with Almex Control boxes, such as the SG1 or T6GFXP, wirelessly to provide real-time display of critical temperature and pressure parameters during splices.

The Almexpad Senior 3.0 comes with the Splice Monitor Application to provide Quality Assurance data and reporting for the splice cook in order to prevent failed splices and ensure the highest splice integrity possible.

FEATURES:

- Networking capability to ensure an even heat pattern where a splice utilizes multiple presses and control boxes
- Real-time pressure readings from the

- Almex pressure bag to ensure there is even pressure over the entire splice.
- Energy consumption is displayed to ensure that there are no platens with heating issues during the cure
- A Record of the entire splice; duration and data points, that can be stored as part of a comprehensive splice quality assurance record or used to reproduce future splices
- Large 10" responsive touch screen
- IP67 rating for harsh environments

- Hot-swappable battery
- Bright screen readable in direct sunlight
- Docking station for charging & connectivity
- Long battery life –over 8 hours
- Connects via WIFI, GSM phone or Bluetooth
- Drop-test rated
- Networks with Almex SG1 or T6GFX control boxes

PRODUCT CODE	DESCRIPTION	FEATURES		
SR-A10	Almexpad Sr 3.0 A10 (Base Unit)	10" Display unit as described above.		
SR-A10-MAX	Almexpad Sr 3.0 MAX	10" Display unit as described above. RFID Scanner, Barcode Scanner		
SR-A10-ULTRAMAX	Almexpad Sr 3.0 ULTRAMAX	10" Display unit as described above. RFID Scanner, Barcode Scanner High Frequency GPS		
PRODUCT CODE	DESCRIPTION	FEATURES		
	Llear Licanca for Splica OA	rolica Manitar rapart store data		

		High Frequency GPS	
PRODUCT CODE	DESCRIPTION		FEATURES
SR-SPLICEQA-01	User License for Splice QA s monitoring & reporting app		Monitor, report, store data on your splices.
20-ACC-ENV-01	Lascar – USB temp and hum readings data logger	idity	-35 to +80°C (-31 to +176°F) Measurement Range, +/-3 RH accuracy
SR-810-SD-128GB	Micro SD Cards 128 GB Sto	rage	128 GB
SR-810-SD-256GB	Micro SD Cards 256 GB Sto	rage	256 GB
SR-810-SD-512-GB	Micro SD Cards 512 GB Sto	rage	512 GB
SR-810-DOCK-STATION	Senior Tablet Docking Static	n	Docking Station
SR-810-BATTERY	Senior Tablet Battery		Replacement Battery
SR-810-HAND-STRAP	Senior Tablet Hand Strap		Strap for Tablet
SR-810-USB-CABLE	Senior Tablet USB Cable		USB Cable

NA NTE: This data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Shaw Almex Europe B.V. 31 646648648 Shaw Almex Industries, Canada \$1 905 643 7750 Shaw Almex Industries, Canada •1 705 746 5884 Shaw Almex Fusion, LLC. U.S.A. 1 404 292 8600 Shaw Almex Africa (Pty) Ltd. • 27 11 794 8262

