

# HPP20-4

The Original Almex Fluid Pressure/Cooling System for Heavyweight Belt Vulcanizers. Equipped with a fluid level gauge, pressure gauge, pressure control valve and pressure safety valve.

## FEATURES:

- Welded aluminum frame construction
- Fluid (water or water/glycol) reservoir
- Rugged, reliable piston pump
- 3/4 HP motor
- Pressurize an overall platen area up to 2.5m<sup>2</sup> (4000 in<sup>2</sup>).
- Voltage, phase and cycle options to work with your vulcanizer

## OPTIONS:

- 50 or 60 Hz motor
- Valves for Water cooling (HPPC20-4)
- Ground-Fault

## PRODUCT INFORMATION

- Capacity: 11.4 Liters/minute (3 US Gallons/minute)
- Tank Volume: 75 Liters (20 US Gallons)
- Weight: 125 Lbs.(57 kg) -empty
- Pressure ranges: 7-14 kg/cm<sup>2</sup> (100-200 psi)
- Large flat-free wheels for ease of transportation



MODEL	DESCRIPTION
HPP20-4	75 Liter (20 US gallon) pump
HPP20-4-GF	75 Liter (20 US gallon) pump with Ground Fault circuitry
HPPC20-4	75 Liter (20 US gallon) pump with cooling option for pressurizing and cooling
HPPC20-4-GF	75 Liter (20 US gallon) pump with cooling option for pressurizing and cooling and Ground Fault circuitry
HPP RES	Additional 75 Liter (20 US gallon) capacity pump reservoir unit

NA

Shaw Almex  
Europe B.V.  
☎ 31 646648648

Shaw Almex  
Industries, Canada  
☎ 1 905 643 7750

Shaw Almex  
Industries, Canada  
☎ 1 705 746 5884

Shaw Almex  
Fusion, LLC. U.S.A.  
☎ 1 404 292 8600

Shaw Almex  
Africa (Pty) Ltd.  
☎ 27 11 794 8262


**ALMEX**  
GROUP  
[www.almex.com](http://www.almex.com) 1.800.977.5423