



P R E S S U R E P U M P S



HPP20-4

COOLING AND PRESSURE PUMP

The **Original Almex Fluid Pressure/Cooling System** for Heavyweight Belt Vulcanizers. Equipped with a fluid level gauge, pressure gauge, pressure control valve and pressure safety valve.

FEATURES:

- Welded aluminum frame construction
- Fluid (water or water/glycol) reservoir
- Rugged, reliable piston pump
- 3/4 HP motor
- Pressurize an overall platen area up to 2.5m² (4000 in²).
- Voltage, phase and cycle options to work with your vulcanizer
- 11.4 Litres/minute (3 US Gallons/min)
- Pressure ranges 7-14 kg/cm² (100-200 psi)
- Dry Weight - 57 kg (125 lbs)

OPTIONS:

- 50 or 60 Hz motor
- Valves for Water cooling (HPPC20-4)
- Ground-Fault



MODEL	DESCRIPTION
HPP20-4 COOLING AND PRESSURE PUMP	
HPP20-4	75 Litre (20 US gallon) pump
HPP20-4-GF	75 Litre (20 US gallon) pump with Ground Fault circuitry
HPP20C-4	75 Litre (20 US gallon) pump with cooling option for pressurizing and cooling
HPPC20-4-GF	75 Litre (20 US gallon) pump with cooling option for pressurizing and cooling and Ground Fault circuitry
HPP RES	Additional 75 Litre (20 US gallon) capacity pump reservoir unit