

Belt Winder and Stand Questionnaire

To ensure the best winder and stand are quoted and supplied, please fill out the following form. Required fields have a red border.

Nam	e:								
Company:		Email:							
Location:		Phone:							
1.	a. Max Roll Diameter Required,					mm	Incl	nes	
OR	1. b. Belt Width					mm	Inches		
2.	Belt Thickness					mm	Inches		
3.	Type of Belt Roll Core		Steel Reel	Stee	l/Wo	oden Co	Core Race Trac		Track
4. R	coll Outside Dimensions	L	W	!	Н		mm	Ir	nches
(Dimensions are used to determine width between posts required to load and unload rolls of belt.									
5.	Max Roll Weight					kg	Lb	S.	
6. diai	Line Pull Required at full meter (if known)					Nm	Lb	s./Ft.	
7. Wir	Shaft Size required for ader/Stand					mm	lnc	hes	
8.	Power Requirements		Volts						
	8 a. Volts				Hz				
	8 b. Hz			Phase					
	8 c. Phase			Pna	ise				
9.	Type of Drive preference		Chain (Fagy Fit) Chain (n (Broak	to Los	رم ا	
			Chain (Easy Fi	L)	Chain (Break to Load)			iu)	
			Direct Drive		Hydraulic				

Almex Group reserves the right to quote drives suitable for the application. Pleasesend the completed form to services@almex.com.

