

ALMEX BELT WINDER & STAND SMALL

Almex has a complete line of Belt Winders and Stands for all types of conveyors, belt sizes and lengths. Drawing on decades of field service experience, Almex winders are designed for the serious belt technician. The small and medium winders are designed to fit on your Chevy 3500 or Ford 350 truck to be your go-to, day-in-day-out winders, for most small belts.


Need to change a large overland or slope belt? You will need one or two of the powerful winders designed to be transported on a drop-deck truck without an oversize permit. Almex has the winder and stand solution to suit your needs.

The Almex Small Belt Winder is designed to fit on ½ the width of the back of a Chevrolet 3500 or Ford 350 truck and be portable.

The Almex Small Belt Stand can be placed next to the winder on the same truck to efficiently get your equipment to the job site.

■ FEATURES:

- The ultimate winder for small plant belts. Aggregate, cement, grain, trash/recycling, agriculture, etc.
- For tight spaces where your medium winder just won't fit.
- Fill up the winder with the largest width and diameter fabric belt you can fit. Designed so you, or your crew, won't hurt it.
- Enough power to get the job done.
- Variable speed control for added safety.
- Units are designed for years of reliable trouble-free operation
- Stainless steel waterproof enclosures
- Available with electric, electric VFD, or hydraulic drive systems
- Units are guarded and protected for operator safety



NA

Shaw Almex
Europe B.V.
☎ 31 646648648

Shaw Almex
Industries, Canada
☎ 1 905 643 7750

Shaw Almex
Industries, Canada
☎ 1 705 746 5884

Shaw Almex
Fusion, LLC. U.S.A.
☎ 1 404 292 8600

Shaw Almex
Africa (Pty) Ltd.
☎ 27 11 794 8262

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423



Belt Winders are designed and manufactured according to the specifications required. Call us to speak to a representative for quote and customized solution. Since Belt winders and stands are customized, orders may take longer to fulfill.

Item	Specification
Reel Specifications	
Max Reel Weight	6 Tons
Max Reel Diameter	94.5"
Max Belt Width	59"
Winder Performance	
Line Pull at Hub	5.4 Tons @ 10%
Line Pull at Max Diameter	0.56 Tons @ 94.5%
Maximum Reeling Speed	5.9 RPM
Drive Torque at Reel	4985 lb-ft
Drive Specifications	
Electrical Motor Power	5.4 HP
Motor Voltage	480 VAC
Equipment Dimensions	
Length	136.5"
Width	48.5"
Height	68.4"
Mass	2.5 Tons

NA

Shaw Almex
Europe B.V.
☎ 31 646648648

Shaw Almex
Industries, Canada
☎ 1 905 643 7750

Shaw Almex
Industries, Canada
☎ 1 705 746 5884

Shaw Almex
Fusion, LLC. U.S.A.
☎ 1 404 292 8600

Shaw Almex
Africa (Pty) Ltd.
☎ 27 11 794 8262


ALMEX
GROUP
www.almex.com 1.800.977.5423