

T6GFXP

CONTROL PANELS

The T6GFXP ground fault control panel features a WIFI signal that will work with the Almexpad to manage and monitor pressure and temperature readings. This T6GFXP is our safest ground fault control panel yet, with ground fault protection internally and at all connection points. Any 25 milliamp leak and the power to that portion will shut off power off in <50 milliseconds.

PRODUCT INFO:

T6-GFXP:

- Operates 1 set of GF platens. 30 amps total (13.7 amps maximum per platen) or 60 amps total (27 amps per platen maximum)
- WIFI connectivity to Almexpad and Android devices
- Includes pump and thermocouple receptacles (4-2 per platen) and pressure sensor
- Network connections to synchronize with multiple control panels (Two platen cables and one power supply cable-all removeable)
- Reads currents of 2 phases for each outlet
- Run up to 8 boxes – 16 platens and maintains a
- Adjustable temperature deviation (default 2.7°C)
- Control fuses are easily accessible

Dimensions: 579 mm (22.8")
x 465 mm (18.3") x 297 mm (11.7")
Weight: 25.4 kg (56 Lbs.)



MODEL	DESCRIPTION	PHASE	AMPS
T6GFXP	T6 Control Panel with Ground Fault	Single or 3 Phase	30 amps or 60 amps

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423