ALMEX

LMEX 12 TEMPERATURE CONTR

RESET

ALMEX T2 TEMPERATURE CONTROL

T2 CONTROL PANEL

T2 Series control panels are available as 30 amp or 40 amp versions with various optional add-ons. All T Series control panels are certified to UL, CSA, and CE standards.

PRODUCT INFO:


T2: Remote Temperature Control Panel

Dual Omron digital temperature control and indication. Small, lightweight, rugged aluminum control panel housing with handle. 115 or 230 volts, single phase ,30 amps total (13.7 amps per platen maximum) or 40 amps total (18 amps per platen maximum). Dimensions: 203 mm (8") x 178 mm (7") x 254 mm (10") Weight: 4 kg (9 Lbs.)

OPTIONS:

- T2T: Includes timer and Audio Alarm
- T2TP: T2T with Pump Receptacle
- T2TC: T2T with automatic water cooling and air purge panel. Designed for use with in-line or plant water systems. Dimensions: 215 mm (8.5") x 215 mm (8.5") x 114 mm (4.5"). Weight: 5.9 kg (13 Lbs.)
- T2-GF: Operates 1 set of Ground Fault (GF) platens (SP-GF, SSP4-GF, AEV/EV-GF). 115 or 230 volts, single phase, 30 amps total (13.7 amps per platen maximum). Includes two platen cables and one power supply cable (all attached). Dimensions: 203 mm (8") x 178 mm (7") x 394 mm (15.5") Weight: 24 Lbs. (11 kg)

Conforms to Australia/New Zealand standards: AS/NZS 3000, 3007, 2081, 4871, AS 4242.







Shaw Almex Africa (Pty) Ltd. **\$** 27 11 794 8262

