

# T2

## CONTROL PANEL

T2 Series control panels are available as 30 amp or 40 amp versions with various optional add-ons. All T Series control panels are certified to UL, CSA, and CE standards.

### ■ PRODUCT INFO:

#### **T2: Remote Temperature Control Panel**

Dual Omron digital temperature control and indication. Small, lightweight, rugged aluminum control panel housing with handle. 115 or 230 volts, single phase, 30 amps total (13.7 amps per platen maximum) or 40 amps total (18 amps per platen maximum). Dimensions: 203 mm (8") x 178 mm (7") x 254 mm (10")  
Weight: 4 kg (9 Lbs.)

### ■ OPTIONS:

- T2T: Includes timer and Audio Alarm
- T2TP: T2T with Pump Receptacle
- T2TC: T2T with automatic water cooling and air purge panel. Designed for use with in-line or plant water systems. Dimensions: 215 mm (8.5") x 215 mm (8.5") x 114 mm (4.5"). Weight: 5.9 kg (13 Lbs.)
- T2-GF: Operates 1 set of Ground Fault (GF) platens (SP-GF, SSP4-GF, AEV/EV-GF). 115 or 230 volts, single phase, 30 amps total (13.7 amps per platen maximum). Includes two platen cables and one power supply cable (all attached). Dimensions: 203 mm (8") x 178 mm (7") x 394 mm (15.5")  
Weight: 24 Lbs. (11 kg)  
Conforms to Australia/New Zealand standards: AS/NZS 3000, 3007, 2081, 4871, AS 4242.



MODEL	DESCRIPTION	PHASE	AMPS
T2	T2 Temperature Control Panel	Single	30 Amps

GL

Shaw Almex  
Mining Equip. (Tianjin) Co. Ltd.  
☎ +86 (22) 2388-9075

PT. Shaw Almex  
Indonesia  
☎ +61 488 780243

Shaw Almex  
Pacific Pty Ltd. Qld  
☎ 61 7 4774 2011

Shaw Almex  
Pacific Pty Ltd. WA  
☎ 61 8 9358 5860

Shaw Almex  
India PVT. Ltd.  
☎ 91-129-2274624


**ALMEX**  
GROUP  
www.almex.com 1.800.977.5423