

# ECRF COLD BOND CEMENT & HARDENER



**ECRF** is the ideal cement for conveyor belt repair and splicing, and is excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

## FEATURES:

- ECRF is an ethyl acetate-based chloroprene cement, and is available in three sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons
- Flammable



### Cement Properties:

Colour: Black  
 Pot Life: 6 Hours @ 21 °C (70 °F)  
 Working Temperature: -23 °C to 82 °C (-10 °F / 180 °F)  
 Calculated Coverage: 660 gr: 2.8 M<sup>2</sup> (30 ft<sup>2</sup>) 3.3 kg:  
 14 M<sup>2</sup> (150 ft<sup>2</sup>) 175 kg: 697 M<sup>2</sup> (7500 ft<sup>2</sup>)  
 Shelf Life: 24 months in a cool, dark location.

ECRF CEMENT PRODUCT CODE	WEIGHT ( METRIC / IMPERIAL )
CC-ECRF-002	660 gr / 1.5 Lbs.
CC-ECRF-010	3.3 kg / 7.5 Lbs.
CC-ECRF-200	175 kg / 386 Lbs.

### Hardener Properties

Colour: Clear  
 Calculated Coverage:  
 1 bottle per 660 gr (1.5 Lbs.)  
 5 per 3.3 kg (7.7 Lbs.)  
 250 per 175 kg (386 Lbs.)  
 Shelf Life: 24 months in a cool, dark location.

ECRF HARDENER PRODUCT CODE	WEIGHT ( METRIC / IMPERIAL )
CH-ECRF-035	35 gr / 1.2 oz

NA