

# ECRF COLD BOND CEMENT & HARDENER



**ECRF** is the ideal cement for conveyor belt repair and splicing, and is excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

## FEATURES:

- ECRF is an ethyl acetate-based chloroprene cement, and is available in three sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons
- Flammable



### Cement Properties:

Colour: Black

Pot Life: 6 Hours @ 21 °C (70 °F)

Working Temperature: -23 °C to 82 °C (-10 °F / 180 °F)

Calculated Coverage: 660 gr: 2.8 M<sup>2</sup> (30 ft<sup>2</sup>) 3.3 kg:

14 M<sup>2</sup> (150 ft<sup>2</sup>) 175 kg: 697 M<sup>2</sup> (7500 ft<sup>2</sup>)

Shelf Life: 24 months in a cool, dark location.

### Hardener Properties

Colour: Clear

Calculated Coverage:

1 bottle per 660 gr (1.5 Lbs.)

5 per 3.3 kg (7.7 Lbs.)

250 per 175 kg (386 Lbs.)

Shelf Life: 24 months in a cool, dark location.

ECRF CEMENT PRODUCT CODE	WEIGHT ( METRIC / IMPERIAL )
CC-ECRF-002	660 gr / 1.5 Lbs.
CC-ECRF-010	3.3 kg / 7.5 Lbs.
CC-ECRF-200	175 kg / 386 Lbs.

ECRF HARDENER PRODUCT CODE	WEIGHT ( METRIC / IMPERIAL )
CH-ECRF-035	35 gr / 1.2 oz

SA

Almex Fusion de Mexico  
☎ 01 (477) 962 97 43

Almex Peru S.A.C.  
☎ 51 999 894040

Shaw Almex Chile SpA  
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada  
☎ +51 31 3120 3737

 **ALMEX**  
GROUP  
www.almex.com 1.800.977.5423