

ECRF COLD BOND CEMENT & HARDENER



ECRF is the ideal cement for conveyor belt repair and splicing, and is excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

FEATURES:

- ECRF is an ethyl acetate-based chloroprene cement, and is available in three sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons
- Flammable



Cement Properties:

Colour: Black

Pot Life: 6 Hours @ 21 °C (70 °F)

Working Temperature: -23 °C to 82 °C (-10 °F / 180 °F)

Calculated Coverage: 660 gr: 2.8 M² (30 ft²) 3.3 kg:

14 M² (150 ft²) 175 kg: 697 M² (7500 ft²)

Shelf Life: 24 months in a cool, dark location.

Hardener Properties

Colour: Clear

Calculated Coverage:

1 bottle per 660 gr (1.5 Lbs.)

5 per 3.3 kg (7.7 Lbs.)

250 per 175 kg (386 Lbs.)

Shelf Life: 24 months in a cool, dark location.

ECRF CEMENT PRODUCT CODE	WEIGHT (METRIC / IMPERIAL)
CC-ECRF-002	660 gr / 1.5 Lbs.
CC-ECRF-010	3.3 kg / 7.5 Lbs.
CC-ECRF-200	175 kg / 386 Lbs.

ECRF HARDENER PRODUCT CODE	WEIGHT (METRIC / IMPERIAL)
CH-ECRF-035	35 gr / 1.2 oz

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

ALMEX
GROUP
www.almex.com 1.800.977.5423