

SA 2000+ COLD BOND CEMENT & HARDENER

SA 2000+ is designed to be a fast-curing cement that will let you return a lagged pulley to service safely. It is ideal for bonding rubber to steel, rubber to rubber, rubber to fabric and fabric to fabric. It will also bond wood, fiberglass, concrete and urethane.

FEATURES:

- SA 2000+ is a chloroprene-based cement
- High initial and permanent adhesion
- Mixed in Almex locations globally for freshness and quick shipment
- Non-flammable



Cement Properties:

Colour: Dark Grey
 Pot Life: 2-3 Hours @ 21 °C (70 °F)
 Working Temperature: -40 °C to 82 °C (-40 °F to 180 °F)
 Calculated Coverage:
 1 kg: 2.8 M² (30 ft²)
 5 kg: 14 M² (150 ft²)
 290 kg: 697 M² (7500 ft²)
 Shelf Life: 24 months in a cool, dark location.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CC-SA2000+-002	1 kg / 2.2 Lbs.
CC-SA2000+-010	5 kg / 11 Lbs.
CC-SA2000+-200	290 kg / 640 Lbs.

Hardener Properties:

Colour: Amber-tinted Clear
 Calculated Coverage:
 1 bottle per 1 kg (2.2 Lbs.)
 5 per 5 kg (11 Lbs.)
 290 per 290 kg (640 Lbs.)
 Shelf Life: 24 months in a cool, dark location.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CH-SA2000+-035	35 gr / 1.2 oz

KIT PRODUCT CODE	DESCRIPTION	WEIGHT (METRIC/IMPERIAL)
CC-SA2000+-002KIT	Cold Bond Cement (1 kg / 2.2 Lbs.) & Hardener (35 gr / 1.2 oz)	1.35 kg / 2.3 Lbs.

NA

Shaw Almex
Europe B.V.
☎ 31 646648648

Shaw Almex
Industries, Canada
☎ 1 905 643 7750

Shaw Almex
Industries, Canada
☎ 1 705 746 5884

Shaw Almex
Fusion, LLC. U.S.A.
☎ 1 404 292 8600

Shaw Almex
Africa (Pty) Ltd.
☎ 27 11 794 8262

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423