

# SA 4000+ COLD BOND CEMENT & HARDENER



**SA 4000+** is designed to be a fast-curing cement for returning a lagged pulley to service safely. It is ideal for bonding rubber to steel, rubber to rubber, rubber to fabric and fabric to fabric. It will also bond wood, fiberglass, concrete and urethane.

## FEATURES:

- SA 4000+ is an ethyl acetate-based chloroprene cement
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Mixed in Almex locations globally for freshness and quick shipment
- Flammable



### Cement Properties:

Colour: Dark Grey

Flammable

Pot Life: 2-3 Hours @ 21 °C (70 °F)

Working Temperature: -40 °C to 82 °C (-40 °F to 180 °F)

Calculated Coverage:

660 gr: 2.8 M<sup>2</sup> (30 ft<sup>2</sup>)

3.3 kg: 14 M<sup>2</sup> (150 ft<sup>2</sup>)

175 kg: 697 M<sup>2</sup> (7500 ft<sup>2</sup>)

Shelf Life: 24 months in a cool dark location.

### Hardener Properties:

Colour: Amber-tinted Clear

Calculated Coverage:

1 bottle per 660 gr (1.5 Lbs.)

5 per 3.3 kg (7.7 Lbs.)

250 per 175 kg (386 Lbs.)

Shelf Life: 24 months in a cool dark location.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CC-SA4000+-002	660 gr / 1.5 Lbs.
CC-SA4000+-010	3.3 kg / 7.5 Lbs.
CC-SA4000+-200	175 kg / 386 Lbs.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CH-SA4000+-035	35 gr / 1.2 oz

KIT PRODUCT CODE	DESCRIPTION	WEIGHT (METRIC/IMPERIAL)
CC-SA4000+-002KIT	Cold Bond Cement (660 gr / 1.5 Lbs.) & Hardener (35 gr / 1.2 oz)	1.1 kg / 2.3 Lbs.

SA

Almex Fusion de Mexico  
☎ 01 (477) 962 97 43

Almex Peru S.A.C.  
☎ 51 999 894040

Shaw Almex Chile SpA  
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada  
☎ +51 31 3120 3737

 **ALMEX**  
GROUP  
www.almex.com 1.800.977.5423