

RM

RUBBER TO METAL PRIMER

RM is the ideal metal primer for use in rubber tanks or chute lining, pulley lagging, and all applications where a bond to metal requires superior adhesion.

FEATURES:

- Use as an interface between rubber and metal, RM offers high bond strength between both surfaces
- RM utilizes polymers and organic compounds to achieve a high strength bond unlike zinc-based primers
- Can be used on steel, aluminum, titanium, wood and other substrates
- Can be applied with a brush, roller or spray



Cement Properties:

Colour: Grey

Flash Point: 5.5 °C (42 °F)

Shelf Life: 12 months from date of manufacture, stored at 21 °C to 26 °C (70 °F to 80 °F).

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CP-RM-Q	750 gr / 1.65 Lbs.
CP-RM-G	3.75 kg / 8.3 Lbs.

SA

Almex Fusion de Mexico
☎ 01 (477) 962 97 43
Mexico

Almex Peru S.A.C.
☎ 51 999 894040
Ate-Vitarte Lima, Peru

Shaw Almex Chile SpA
☎ +56 2 2 745 3969
Santiago, Chile

ALMEX GROUP
Shaw Almex Industries Ltd.
1.800.977.5423
www.almex.com sales@almex.com