

RM

RUBBER TO METAL PRIMER

RM is the ideal metal primer for use in rubber tanks or chute lining, pulley lagging, and all applications where a bond to metal requires superior adhesion.

FEATURES:

- Use as an interface between rubber and metal, RM offers high bond strength between both surfaces
- RM utilizes polymers and organic compounds to achieve a high strength bond unlike zinc-based primers
- Can be used on steel, aluminum, titanium, wood and other substrates
- Can be applied with a brush, roller or spray



Cement Properties:

Colour: Grey

Flash Point: 5.5 °C (42 °F)

Shelf Life: 12 months from date of manufacture, stored at 21 °C to 26 °C (70 °F to 80 °F).

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CP-RM-Q	750 gr / 1.65 Lbs.
CP-RM-G	3.75 kg / 8.3 Lbs.

NA

Shaw Almex
Europe B.V.

☎ 31 646648648
Drachten, The Netherlands

Shaw Almex
Industries

☎ 1 905 643 7750
Stoney Creek, Ontario

Shaw Almex
Industries

☎ 1 705 746 5884
Parry Sound, Ontario

Shaw Almex
Fusion, LLC.

☎ 1 404 292 8600
Decatur, Georgia, USA

Shaw Almex
Africa (Pty) Ltd.

☎ 27 11 794 8262
South Africa



ALMEX
GROUP

Shaw
Almex
Industries Ltd.

1.800.977.5423
www.almex.com

sales@almex.com