

WECRF

COLD BOND CEMENT & HARDENER

WECRF is the ideal cement for conveyor belt repair and splicing. It is also excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

FEATURES:

- WECRF is an ethyl-based chloroprene cement and is available in three different sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons
- Flammable



Cement Properties:

Colour: White
 Pot Life: 4 Hours @ 21 °C (70 °F)
 Working Temperature: -23 °C to 82 °C (-10 °F to 180 °F)
 Calculated Coverage:
 660 gr: 2.8 M² (30 ft²)
 3.3 kg: 14 M² (150 ft²)
 175 kg: 697 M² (7500 ft²)
 Shelf Life: 24 months in a cool dark location.

Hardener Properties:

Colour: Amber-tinted Clear
 Calculated Coverage:
 1 bottle per 660 gr (1.5 Lbs.)
 5 per 3.3 kg (7.7 Lbs.)
 250 per 175 kg (386 Lbs.)
 Shelf Life: 24 months in a cool dark location.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CC-WECRF-002	660 gr / 1.5 Lbs.
CC-WECRF-010	3.3 kg / 7.5 Lbs.
CC-WECRF-200	175 kg / 386 Lbs.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CH-WECRF-035	35 gr / 1.2 oz

KIT PRODUCT CODE	DESCRIPTION	WEIGHT (METRIC/IMPERIAL)
CC-WECRF-002KIT	Cold Bond Cement (660 gr / 1.5 Lbs.) & Hardener (35 gr / 1.2 oz)	1.1 kg / 1.6 Lbs.

NA