

WECRF

COLD BOND CEMENT & HARDENER

WECRF is the ideal cement for conveyor belt repair and splicing. It is also excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

FEATURES:

- WECRF is an ethyl-based chloroprene cement and is available in three different sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons
- Flammable



Cement Properties:

Colour: White

Pot Life: 4 Hours @ 21 °C (70 °F)

Working Temperature: -23 °C to 82 °C (-10 °F to 180 °F)

Calculated Coverage:

660 gr: 2.8 M² (30 ft²)

3.3 kg: 14 M² (150 ft²)

175 kg: 697 M² (7500 ft²)

Shelf Life: 24 months in a cool dark location.

Hardener Properties:

Colour: Amber-tinted Clear

Calculated Coverage:

1 bottle per 660 gr (1.5 Lbs.)

5 per 3.3 kg (7.7 Lbs.)

250 per 175 kg (386 Lbs.)

Shelf Life: 24 months in a cool dark location.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CC-WECRF-002	660 gr / 1.5 Lbs.
CC-WECRF-010	3.3 kg / 7.5 Lbs.
CC-WECRF-200	175 kg / 386 Lbs.

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
CH-WECRF-035	35 gr / 1.2 oz

KIT PRODUCT CODE	DESCRIPTION	WEIGHT (METRIC/IMPERIAL)
CC-WECRF-002KIT	Cold Bond Cement (660 gr / 1.5 Lbs.) & Hardener (35 gr / 1.2 oz)	1.1 kg / 1.6 Lbs.

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423