

HC1-FREE VULCANIZING SPLICE CEMENT

HC1-FREE is a Toluene free, one-part cement for vulcanized belt splicing. It is designed for use as a tackifying agent for cured and uncured rubber materials.

FEATURES:

- Toluene-Free formula
- Builds additional tack for uncured splice materials in preparation for a conveyor belt splice
- Brushable consistency for ease of application
- Good penetration into the splice materials
- Can be used with a variety of adhesive systems such as Fabric Primer and Steel Cord Primer
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. Neoprene (CR) rubber belt splices
- Flammable

Product Information Properties:

Rubber Colour: Black

Base Polymer: NR/SBR Rubber

Solids (wt.): 15-20%

Calculated Coverage:

700 gr (1.54 Lbs.) - 2.7 M² (29 ft²)

3 kg (6.6 Lbs.) - 13.4 M² (144 ft²)

14.5 kg (31.9 Lbs.) - 67 M² (721 ft²)

170 kg (374 Lbs.) - 670 M² (7212 ft²)

Flash Point: 7 °C (45 °F)

Shelf Life: 6 Months at 21 °C (70 °F)

or 12 Months at 10 °C (50 °F).



PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HC1F-Q	700 gr / 1.54 Lbs.
AA-HC1F-G	3 kg / 6.6 Lbs.
AA-HC1F-5G	14.5 kg / 31.9 Lbs.
AA-HC1F-55G	170 kg / 374 Lbs.

NA

Shaw Almix
Europe B.V.

☎ 31 646648648
Drachten, The Netherlands

Shaw Almix
Industries

☎ 1 905 643 7750
Stoney Creek, Ontario

Shaw Almix
Industries

☎ 1 705 746 5884
Parry Sound, Ontario

Shaw Almix
Fusion, LLC.

☎ 1 404 292 8600
Decatur, Georgia, USA

Shaw Almix
Africa (Pty) Ltd.

☎ 27 11 794 8262
South Africa



ALMEX
GROUP

Shaw
Almix
Industries Ltd.

1.800.977.5423
www.almex.com

sales@almex.com