

# HC1-FREE VULCANIZING SPLICE CEMENT

**HC1-FREE** is a Toluene free, one-part cement for vulcanized belt splicing. It is designed for use as a tackifying agent for cured and uncured rubber materials.

## FEATURES:

- Toluene-Free formula
- Builds additional tack for uncured splice materials in preparation for a conveyor belt splice
- Brushable consistency for ease of application
- Good penetration into the splice materials
- Can be used with a variety of adhesive systems such as Fabric Primer and Steel Cord Primer
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. Neoprene (CR) rubber belt splices
- Flammable

### Product Information Properties:

Rubber Colour: Black

Base Polymer: NR/SBR Rubber

Solids (wt.): 15-20%

Calculated Coverage:

700 gr (1.54 Lbs.) - 2.7 M<sup>2</sup> (29 ft<sup>2</sup>)

3 kg (6.6 Lbs.) - 13.4 M<sup>2</sup> (144 ft<sup>2</sup>)

14.5 kg (31.9 Lbs.) - 67 M<sup>2</sup> (721 ft<sup>2</sup>)

170 kg (374 Lbs.) - 670 M<sup>2</sup> (7212 ft<sup>2</sup>)

Flash Point: 7 °C (45 °F)

Shelf Life: 6 Months at 21 °C (70 °F)

or 12 Months at 10 °C (50 °F).



PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HC1F-Q	700 gr / 1.54 Lbs.
AA-HC1F-G	3 kg / 6.6 Lbs.
AA-HC1F-5G	14.5 kg / 31.9 Lbs.
AA-HC1F-55G	170 kg / 374 Lbs.

SA

Almex Fusion de México  
☎ 01 (477) 962 97 43

Almex Peru S.A.C.  
☎ 51 999 894040

Shaw Almex Chile SpA  
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada  
☎ +51 31 3120 3737

 **ALMEX**  
GROUP  
www.almex.com 1.800.977.5423