

HST

SPLICE SURFACE PREP

HST Splice Surface Prep is an industrial solvent, cleaner and degreaser. It will not leave an oily residue or impede adhesion. HST can be used on all rubber, metal, and fabric surfaces. It is ideal for cleaning the splice area before applying cement and splice materials.

FEATURES:

- Cleans, degreases and readies the surface for priming and tackifying
- Very pure solvent
- Specially formulated for the rubber fabrication and convey or splicing industry
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloro prene i.e. Neoprene (CR) rubber belt splices
- Flammable

Product Information

Properties:

Rubber Colour: Clear

Base Polymer: Solvent

Solids (wt.): 0%

Calculated Coverage:

16.6 M² (288 ft²)

Flash Point: 7 °C (45 °F)

Storage: Store in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces and all sources of ignition.



PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HST-Q	700 gr / 1.54 Lbs.
AA-HST-G	3.0 kg / 6.6 Lbs.
AA-HST-55G	170 kg / 374 Lbs.

NA

Shaw Almex
Europe B.V.
☎ 31 646648648

Shaw Almex
Industries, Canada
☎ 1 905 643 7750

Shaw Almex
Industries, Canada
☎ 1 705 746 5884

Shaw Almex
Fusion, LLC. U.S.A.
☎ 1 404 292 8600

Shaw Almex
Africa (Pty) Ltd.
☎ 27 11 794 8262

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423