

HST

SPLICE SURFACE PREP

HST Splice Surface Prep is an industrial solvent, cleaner and degreaser. It will not leave an oily residue or impede adhesion. HST can be used on all rubber, metal, and fabric surfaces. It is ideal for cleaning the splice area before applying cement and splice materials.

FEATURES:

- Cleans, degreases and readies the surface for priming and tackifying
- Very pure solvent
- Specially formulated for the rubber fabrication and convey or splicing industry
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloro prene i.e. Neoprene (CR) rubber belt splices
- Flammable

Product Information

Properties:

Rubber Colour: Clear

Base Polymer: Solvent

Solids (wt.): 0%

Calculated Coverage:

16.6 M² (288 ft²)

Flash Point: 7 °C (45 °F)

Storage: Store in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces and all sources of ignition.



PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HST-Q	700 gr / 1.54 Lbs.
AA-HST-G	3.0 kg / 6.6 Lbs.
AA-HST-55G	170 kg / 374 Lbs.

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423