

FABRIC BELT TIE GUM

Fabric Belt Tie Gum is an uncured rubber for vulcanized belt splicing.

It is designed for use as a skim rubber replacement material when splicing fabric conveyor belts. The material is designed to bond all standard grades of fabric conveyor belts.

* Premium Fabric Cover also available

FEATURES:

- Enhances working life of fabric belt splices
- Improves flexibility and strength of conveyor belt splices
- Eliminates surface contamination (normal application) with double-sided poly
- Uses poly color coding system to ID compound
- For Natural Rubber (NR), Polyisoprene (IR), Styrene Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. - Neoprene (CR) rubber belt splices

Properties:

Rubber colour: Black

Poly Liner colour: Yellow (double-sided)

Base Polymer: NR Rubber

Specific Gravity: 1.15 - 1.21

Hardness: 65 - 75 Shore A

Rubber Tensile: 2500 - 3000 psi

Rubber Elongation: 300 - 500% (at break)

Shelf Life: 6 Months at 70 °F (21 °C) or

12 Months at 50° F (10 °C).



PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)	POLY COLOUR
AA-FBG-030	0.76 mm x 508 mm x 1524 cm	0.030" x 20" x 50'	Yellow
AA-FBG-040	1.02 mm x 508 mm x 1524 cm	0.040" x 20" x 50'	Yellow
AA-FBG-060	1.52 mm x 508 mm x 1524 cm	0.060" x 20" x 50'	Yellow
AA-FBG-030-39	0.76 mm x 990.6 mm x 1524 cm	0.030" x 39" x 50'	Yellow
AA-FBG-040-39	1.02 mm x 990.6 mm x 1524 cm	0.040" x 39" x 50'	Yellow
AA-FBG-060-39	1.52 mm x 990.6 mm x 1524 cm	0.060" x 39" x 50'	Yellow
AA-PFBG-030	0.76 mm x 508 mm x 1524 cm	0.030" x 20" x 50'	Blue
AA-PFBG-040	1.02 mm x 508 mm x 1524 cm	0.040" x 20" x 50'	Blue
AA-PFBG-060	1.52 mm x 508 mm x 1524 cm	0.060" x 20" x 50'	Blue

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423