

# MSHA CS-21

## TIE GUM

Fusion Systems MSHA Grade, Part 14 Certified, **Fabric Belt Tie Gum** is an uncured rubber for vulcanized belt splicing.

It is designed for use as a skim rubber replacement material in splicing MSHA Grade fabric conveyor belts. This material is designed to be used in both finger and step splices of MSHA Grade fabric conveyor belts.

### FEATURES:

- Enhances the working life of MSHA Grade fabric belt splices
- Improves flexibility and strength of MSHA Grade conveyor belt splices
- Eliminates surface contamination (normal application) with double sided poly
- Uses poly colour coding system to ID compound



#### Product Information

##### Properties:

Base Polymer:

SBR/BR Rubber

Rubber Colour: Black

Poly Liner Colour:

Orange (Double-Sided)

Specific Gravity: 1.39-1.43

Hardness: 57-67 Shore A

Rubber Tensile:

10450-1700 psi

Rubber Elongation:

500 - 700% (at break)

Shelf Life:

6 Mths at 70 °F (21 °C)

or 12 Mths at 50 °F (10 °C).

PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMP. (TxWxL)	POLY COLOUR
AA-FBGMSHA-030	0.76 mm x 508 mm x 15240 mm	0.030" x 20" x 50'	Orange
AA-FBGMSHA-040	1.02 mm x 508 mm x 15240 mm	0.040" x 20" x 50'	Orange
AA-FBGMSHA-060	1.52 mm x 508 mm x 15240 mm	0.060" x 20" x 50'	Orange
AA-FBGMSHA-030-39	0.76 mm x 990.6 mm x 15240 mm	0.030" x 39" x 50'	Orange
AA-FBGMSHA-040-39	1.02 mm x 990.6 mm x 15240 mm	0.040" x 39" x 50'	Orange
AA-FBGMSHA-060-39	1.52 mm x 990.6 mm x 15240 mm	0.060" x 39" x 50'	Orange

NA

Shaw Almex  
Europe B.V.  
☎ 31 646648648

Shaw Almex  
Industries, Canada  
☎ 1 905 643 7750

Shaw Almex  
Industries, Canada  
☎ 1 705 746 5884

Shaw Almex  
Fusion, LLC, U.S.A.  
☎ 1 404 292 8600

Shaw Almex  
Africa (Pty) Ltd.  
☎ 27 11 794 8262

 **ALMEX**  
GROUP  
www.almex.com 1.800.977.5423