

# BELT NOODLE GUM

**Steel Cord Belt Cable Gum** is an uncured rubber for vulcanized belt splicing. It is designed to use as an inter-core cord rubber replacement material in splicing steel cord conveyor belts or a tie gum in fabric belts.

This material is designed to bond to cured inter-core rubber and wire cords in all standard grade steel cord conveyor belts. Use Steel Cord Belt Cable Gum for fabric belt cured skim rubber and general bond improvement material for general grade fabric conveyor belts.

## FEATURES:

- Enhances working life of steel cord belts splices
- Improves flexibility and strength of conveyor belt splices
- Eliminates surface contamination (normal application) with double-sided poly
- Uses poly color coding system to ID compound
- For Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. -Neoprene (CR) rubber belt splices

### Product Information Properties:

Weight (Kg / Lbs.): 0.25 Kg (0.6 Lbs.)

Length (M / Ft): 5 M (16')

Width (mm / In): 6.4 mm (0.25")

Thickness/Gauge (mm / In): 3 mm (0.118")\*

Rubber Color: Black

Poly Liner Color: Blue (double-sided)

Base Polymer: SBR Rubber

Specific Gravity: 1.15 – 1.21

Hardness: 58 – 68 Shore A

Tensile Strength: 2000 – 2600 psi

Elongation: 300 – 500 % (at break)

Shelf Life: 6 months at 70 °F (21 °C).  
or 12 months at 50 °F (10 °C).



Bosch Noodle Extruder (sold separately)  
PT-EXT-110, PT-EXT-220

PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)	POLY COLOUR
AA-STN-365	3.05 mm x 6.35 mm x 4876.8 mm	0.120" x 0.250" x 16'	Blue
AA-STN-365-5	3.05 mm x 12.70 mm x 4876.8 mm	0.120" x 0.500" x 16'	Blue

NA

Shaw Almex  
Europe B.V.  
☎ 31 646648648

Shaw Almex  
Industries, Canada  
☎ 1 905 643 7750

Shaw Almex  
Industries, Canada  
☎ 1 705 746 5884

Shaw Almex  
Fusion, LLC, U.S.A.  
☎ 1 404 292 8600

Shaw Almex  
Africa (Pty) Ltd.  
☎ 27 11 794 8262

 **ALMEX**  
GROUP  
www.almex.com 1.800.977.5423