

BELT NOODLE

GUM

Steel Cord Belt Cable Gum is an uncured rubber for vulcanized belt splicing. It is designed to use as an inter-core cord rubber replacement material in splicing steel cord conveyor belts or a tie gum in fabric belts.

This material is designed to bond to cured inter-core rubber and wire cords in all standard grade steel cord conveyor belts. Use Steel Cord Belt Cable Gum for fabric belt cured skim rubber and general bond improvement material for general grade fabric conveyor belts.

FEATURES:


Enhances working life of steel cord belts splices

• Improves flexibility and strength of conveyor belt splices

 Eliminates surface contamination (normal application) with double-sided poly

• Uses poly color coding system to ID compound

 For Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. -Neoprene (CR) rubber belt splices



Weight (Kg / Lbs.): 0.25 Kg (0.6 Lbs.) Length (M / Ft): 5 M (16') Width (mm / In): 6.4 mm (0.25") Thickness/Gauge (mm / In): 3 mm (0.118")* Rubber Color: Black

Poly Liner Color: Blue (double-sided) Base Polymer: SBR Rubber Specific Gravity: 1.15 – 1.21 Hardness: 58 – 68 Shore A Tensile Strength: 2000 – 2600 psi Elongation: 300 – 500 % (at break) Shelf Life: 6 months at 70 °F (21 °C). or 12 months at 50 °F (10 °C).



PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)	POLY COLOUR
AA-STN-365	3.05 mm x 6.35 mm x 4876.8 mm	0.120" x 0.250" x 16'	Blue
AA-STN-365-5	3.05 mm x 12.70 mm x 4876.8 mm	0.120" x 0.500" x 16'	Blue

SA

Almex Fusion de Mexico • 01 (477) 962 97 43

Almex Peru S.A.C. 51 999 894040

Almex Indústria do Brasil Limitada \$\sim +51 31 3120 3737\$

