

# HFP

## FABRIC BELT PRIMER

**HFP** is a one-part coating for RFL treated fabric that enhances adhesions in vulcanized belt splicing. It is designed for use as a reactive bonding agent between bare fabric surfaces and uncured splice materials.

### FEATURES:

- Prepares the clean work surface for tackifying and increases the bond
- Tested for compatibility with all major conveyor belting manufacturer specifications
- Brushable consistency for ease of application
- Good penetration into RFL treated fabric
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. Neoprene (CR) rubber belt splices
- Flammable

#### Product Information Properties:

Rubber Colour: Black

Base Polymer: Mix of Polymers

Solids (wt.): 20-25%

Calculated Coverage: 13.4 M<sup>2</sup> (144 ft.<sup>2</sup>)

Flash Point: 26 °C (79 °F)

Shelf Life: 6 Months at 21 °C (70 °F) or

12 Months at 10 °C (50 °)

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HFP-Q	750 gr / 1.7 Lbs.



NA

Shaw Almex  
Europe B.V.  
☎ 31 646648648

Shaw Almex  
Industries, Canada  
☎ 1 905 643 7750

Shaw Almex  
Industries, Canada  
☎ 1 705 746 5884

Shaw Almex  
Fusion, LLC, U.S.A.  
☎ 1 404 292 8600

Shaw Almex  
Africa (Pty) Ltd.  
☎ 27 11 794 8262

 **ALMEX**  
GROUP  
www.almex.com 1.800.977.5423