

HFP

FABRIC BELT PRIMER

HFP is a one-part coating for RFL treated fabric that enhances adhesions in vulcanized belt splicing. It is designed for use as a reactive bonding agent between bare fabric surfaces and uncured splice materials.

FEATURES:

- Prepares the clean work surface for tackifying and increases the bond
- Tested for compatibility with all major conveyor belting manufacturer specifications
- Brushable consistency for ease of application
- Good penetration into RFL treated fabric
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. Neoprene (CR) rubber belt splices
- Flammable

Product Information Properties:

Rubber Colour: Black

Base Polymer: Mix of Polymers

Solids (wt.): 20-25%

Calculated Coverage: 13.4 M² (144 ft.²)

Flash Point: 26 °C (79 °F)

Shelf Life: 6 Months at 21 °C (70 °F) or

12 Months at 10 °C (50 °)

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HFP-Q	750 gr / 1.7 Lbs.



SA

Almex Fusion de Mexico
☎ 01 (477) 962 97 43

Almex Peru S.A.C.
☎ 51 999 894040

Shaw Almex Chile SpA
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada
☎ +51 31 3120 3737

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423