

HFP

FABRIC BELT PRIMER

HFP is a one-part coating for RFL treated fabric that enhances adhesions in vulcanized belt splicing. It is designed for use as a reactive bonding agent between bare fabric surfaces and uncured splice materials.

FEATURES:

- Prepares the clean work surface for tackifying and increases the bond
- Tested for compatibility with all major conveyor belting manufacturer specifications
- Brushable consistency for ease of application
- Good penetration into RFL treated fabric
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. Neoprene (CR) rubber belt splices
- Flammable

Product Information Properties:

Rubber Colour: Black

Base Polymer: Mix of Polymers

Solids (wt.): 20-25%

Calculated Coverage: 13.4 M² (144 ft.²)

Flash Point: 26 °C (79 °F)

Shelf Life: 6 Months at 21 °C (70 °F) or

12 Months at 10 °C (50 °F)



PRIMER | FLAMMABLE

CONTENTS: 750 gr | AA-HFP-Q

PRODUCT CODE

AA-HFP-Q

WEIGHT (METRIC/IMPERIAL)

750 gr / 1.7 Lbs.

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423