

FUSIONLAGG WMD WHITE MINI DIAMOND

FusionLagg WMD (White Mini Diamond) is a small profile pulley lagging, ideal for drive pulleys with medium to low tensions and belt ratings.

FEATURES:

- Press cured, FusionLagg WMD is compounded specifically for use in food, tobacco, or pharmaceutical applications
- Featuring our Fusion Systems proprietary bonding layer technology significantly enhancing the bond between the lagging and the pulley shell
- Nitrile rubber content, molded in a mini-diamond pattern for exceptional grip and wear resistance
- Provided with the Fusion bonding layer on the reverse side for superior adhesion to the pulley surface

 Drive pulleys require a small profile and FusionLagg WMD is particularly well-suited for food handling applications, wet or dry




PROPERTIES:

Colour: White Elastomer: Nitrile Tensile Strength: 10.5 Mpa

Elongation at Break: 620 % Density: 1.20 g / cm³ Hardness: 53 Shore A Abrasion Resistance: 300 mm³

Groove Dimensions: 4 mm x 3 mm (3/16" x 1/8") Diamond Dimensions: 40 mm x 20 mm (1" x 3/4")



PRODUCT CODE

DIMENSIONS - METRIC (TxWxL)

DIMENSIONS - IMPERIAL (TxWxL)

CFL-WMD-3116

8 mm x 1300 mm x 5 M

5/16" x 51" x 16.5'

NA

Shaw Almex Europe B.V. • 31 646648648 Shaw Almex Industries, Canada \$1 905 643 7750 Shaw Almex Industries, Canada **1** 705 746 5<u>884</u> Shaw Almex Fusion, LLC. U.S.A. 1 404 292 8600 Shaw Almex Africa (Pty) Ltd. \$ 27 11 794 8262

