

# FUSIONLAGG WMD

## WHITE MINI DIAMOND

**FusionLagg WMD** (White Mini Diamond) is a small profile pulley lagging, ideal for drive pulleys with medium to low tensions and belt ratings.

### FEATURES:

- Press cured, FusionLagg WMD is compounded specifically for use in food, tobacco, or pharmaceutical applications
- Featuring our **Fusion Systems proprietary bonding layer technology** significantly enhancing the bond between the lagging and the pulley shell
- Nitrile rubber content, molded in a mini-diamond pattern for exceptional grip and wear resistance
- Provided with the Fusion bonding layer on the reverse side for superior adhesion to the pulley surface
- Drive pulleys require a small profile and FusionLagg WMD is particularly well-suited for food handling applications, wet or dry

**SPECIAL ORDER** SPECIAL ORDER ITEMS MAY EXPERIENCE DELAYED DELIVERY TIME.

### PROPERTIES:

Colour: White  
 Elastomer: Nitrile  
 Tensile Strength: 10.5 Mpa  
 Elongation at Break: 620 %  
 Density: 1.20 g / cm<sup>3</sup>  
 Hardness: 53 Shore A  
 Abrasion Resistance: 300 mm<sup>3</sup>  
 Groove Dimensions: 4 mm x 3 mm (3/16" x 1/8")  
 Diamond Dimensions: 40 mm x 20 mm (1" x 3/4")

PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)
CFL-WMD-3116	8 mm x 1300 mm x 5 M	5/16" x 51" x 16.5'

SA

Almex Fusion de Mexico  
 ☎ 01 (477) 962 97 43

Almex Peru S.A.C.  
 ☎ 51 999 894040

Shaw Almex Chile SpA  
 ☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada  
 ☎ +51 31 3120 3737

**ALMEX**  
 GROUP  
 www.almex.com 1.800.977.5423