

SPLICING FOIL

Fusion Splicing Foil is excellent for replacing damaged or worn layers in a conveyor belt when building up a repair. Use in conjunction with Fusion Cover Rubber compound.

FEATURES:

- Higher abrasion index than most belt covers
- Recommended for use in cold splicing of conveyor belts
- Bonding layer compound
- Recommended for repair of conveyor belts or tank linings (under certain conditions)
- Use in conjunction with Fusion Cover Rubber compound, and SA 2000+, SA 4000+ or ECRF adhesives



PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)
CF-SF-032316	0.08 mm x 500 mm x 5 M	1/32" x 20" x 16.5'
CF-SF-032333	0.08 mm x 500 mm x 10 M	1/32" x 20" x 33'

NA

Shaw Almex
Europe B.V.

☎ 31 646648648
Drachten, The Netherlands

Shaw Almex
Industries

☎ 1 905 643 7750
Stoney Creek, Ontario

Shaw Almex
Industries

☎ 1 705 746 5884
Parry Sound, Ontario

Shaw Almex
Fusion, LLC.

☎ 1 404 292 8600
Decatur, Georgia, USA

Shaw Almex
Africa (Pty) Ltd.

☎ 27 11 794 8262
South Africa



Shaw
Almex
Industries Ltd.

1.800.977.5423
www.almex.com

sales@almex.com