

COMBI SCRAPER

85/55/85

Fusion Combi 85/55/85 is a vulcanized laminate of two hard outer layers, containing a softer inside grey layer. Perfect for larger stickier material applications.

FEATURES:

- Produced with the finest natural rubber
- Multi-layer construction provides long wear life with excellent cleaning capabilities
- Hard outside layers provide impact protection
- Soft inside layer provides superior squeegee-type cleaning

PROPERTIES:

Colour: Black-Grey-Black

Elastomer: SBR-SBR

Tensile Strength: 19.5 Mp -15 Mpa

Elongation at Break: 400 % - 530 %

Density: 1.17 g / cm³ - 1.1 g / cm³

Hardness: 85 Shore A - 55 Shore A

Abrasion Resistance: 100 mm³ - 160 mm³

SPECIAL ORDER SPECIAL ORDER ITEMS MAY EXPERIENCE DELAYED DELIVERY TIME.

PRODUCT CODE	DIMENSIONS - METRIC (T x W x L)	DIMENSIONS - IMPERIAL (T x W x L)
CCR-8555-7506	20 mm x 150 mm x 15.25 M	3/4" x 6" x 50'
CCR-8555-7508	20 mm x 200 mm x 15.25 M	3/4" x 8" x 50'
CCR-8555-755950	20 mm x 1500 mm x 15.25 M	3/4" x 59" x 50'
CCR-8555-1006	25 mm x 150 mm x 15.25 M	1" x 6" x 50'
CCR-8555-1008	25 mm x 200 mm x 15.25 M	1" x 8" x 50'
CCR-8555-105950	25 mm x 1500 mm x 15.25 M	1" x 59" x 50'
CCR-8555-1506	40 mm x 150 mm x 15.25 M	1 1/2" x 6" x 50'
CCR-8555-1508	40 mm x 200 mm x 15.25 M	1 1/2" x 8" x 50'
CCR-8555-155950	40 mm x 1500 mm x 15.25 M	1 1/2" x 59" x 50'
CCR-8555-2006	50 mm x 150 mm x 15.25 M	2" x 6" x 50'
CCR-8555-2008	50 mm x 200 mm x 15.25 M	2" x 8" x 50'
CCR-8555-205950	50 mm x 1500 mm x 15.25 M	2" x 59" x 50'

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075
Tianjin, P.R. China

PT. Shaw Almex
Indonesia
☎ +61 488 780243
Indonesia

Shaw Almex
Pacific Pty Ltd.
☎ 61 7 4774 2011
Mount St. John, Qld, Australia

Shaw Almex
Pacific Pty Ltd.
☎ 61 8 9358 5860
Welshpool, WA, Australia

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624
Haryana, India



ALMEX
GROUP

Shaw
Almex
Industries Ltd.

1.800.977.5423
www.almex.com

sales@almex.com