

FUSIONWEAR 35

FusionWear 35 is a premium grade pre-cured natural rubber compound for lining, ideal for slurry handling and other wet material handling applications.

FEATURES:

- Specially formulated for superior wear and abrasion resistance properties
- Excellent elasticity and resilience, providing years of economical service in high wear areas
- Fusion Wear is manufactured with a proprietary bonding layer technology, available on one or both sides
- Proven results in material handling applications such as pipelines, launders, sumps, pumps, hydrocyclones, flotation cells, tank and chute linings
- Available in 10 M (32.8') length rolls upon request



Photo courtesy of Cal Splice & Components Inc, California USA

PROPERTIES:

Colour: Tan

Elastomer: NR

Tensile Strength: 19 Mpa (2700 psi)

Elongation at Break: 650 %

Density: 1.00 g / cm³

Hardness: 38 (-3) Shore A

Abrasion Resistance: 85 mm³ @ 5 N

Resilience: 70 %

PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)
CFW-35SB-1250	3 mm x 1500 mm x 15.25 M	1/8" x 59" x 50'
CFW-35SB-2550	6 mm x 1500 mm x 15.25 M	1/4" x 59" x 50'
CFW-35SB-5050	12 mm x 1500 mm x 15.25 M	1/2" x 59" x 50'
CFW-35SB-7550	20 mm x 1500 mm x 15.25 M	3/4" x 59" x 50'
CFW-35SB-1050	25 mm x 1500 mm x 15.25 M	1" x 59" x 50'

SPECIAL ORDER SPECIAL ORDER ITEMS MAY EXPERIENCE DELAYED DELIVERY TIME.

NA

Shaw Almex
Europe B.V.
☎ 31 646648648

Shaw Almex
Industries, Canada
☎ 1 905 643 7750

Shaw Almex
Industries, Canada
☎ 1 705 746 5884

Shaw Almex
Fusion, LLC U.S.A.
☎ 1 404 292 8600

Shaw Almex
Africa (Pty) Ltd.
☎ 27 11 794 8262

ALMEX GROUP
www.almex.com 1.800.977.5423