

# FUSIONWEAR 35

**FusionWear 35** is a premium grade pre-cured natural rubber compound for lining, ideal for slurry handling and other wet material handling applications.

## FEATURES:

- Specially formulated for superior wear and abrasion resistance properties
- Excellent elasticity and resilience, providing years of economical service in high wear areas
- Fusion Wear is manufactured with a proprietary bonding layer technology, available on one or both sides
- Proven results in material handling applications such as pipelines, launders, sumps, pumps, hydrocyclones, flotation cells, tank and chute linings
- Available in 10 M (32.8') length rolls upon request



Photo courtesy of Cal Splice & Components Inc, California USA

## PROPERTIES:

Colour: Tan

Elastomer: NR

Tensile Strength: 19 Mpa (2700 psi)

Elongation at Break: 650 %

Density: 1.00 g / cm<sup>3</sup>

Hardness: 38 (-3) Shore A

Abrasion Resistance: 85 mm<sup>3</sup> @ 5 N

Resilience: 70 %

PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)
CFW-35SB-1250	3 mm x 1500 mm x 15.25 M	1/8" x 59" x 50'
CFW-35SB-2550	6 mm x 1500 mm x 15.25 M	1/4" x 59" x 50'
CFW-35SB-5050	12 mm x 1500 mm x 15.25 M	1/2" x 59" x 50'
CFW-35SB-7550	20 mm x 1500 mm x 15.25 M	3/4" x 59" x 50'
CFW-35SB-1050	25 mm x 1500 mm x 15.25 M	1" x 59" x 50'

**SPECIAL  
ORDER**

SPECIAL ORDER ITEMS  
MAY EXPERIENCE DELAYED  
DELIVERY TIME.

SA

Almex Fusion de Mexico  
☎ 01 (477) 962 97 43

Almex Peru S.A.C.  
☎ 51 999 894040

Shaw Almex Chile SpA  
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada  
☎ +51 31 3120 3737

**ALMEX**  
GROUP  
www.almex.com 1.800.977.5423