

FUSIONWEAR 40

FusionWear 40 is a premium quality natural rubber compound, ideal for both wet and dry abrasive applications.

FEATURES:

- Outstanding resilience and resistance to wet abrasion and cutting wear
- Fusion Wear is manufactured with a proprietary bonding layer technology, available on one or both sides
- Proven results in handling applications such as slurries, pipelines, launders, sumps, pumps, hydrocyclones, flotation cells, tank and chute linings as well as bend and snub pulley linings
- Available in 10 M (32.8') length rolls upon request

PROPERTIES:

Colour: Orange

Elastomer: NR Blend

Tensile Strength: 20 Mpa (2900 psi)

Elongation at Break: 600 %

Density: 1.02 g / cm³

Hardness: 45 (+/-5) Shore A

Abrasion Resistance: 65 mm³ @ 5 N



Photo courtesy of Cal Splice & Components Inc, California USA

PRODUCT CODE	DIMENSIONS - METRIC (T x W x L)	DIMENSIONS - IMPERIAL (T x W x L)
CFWO-40SB-1250	3 mm x 1500 mm x 15.25 M	1/8" x 59" x 50'
CFWO-40SB-2550	6 mm x 1500 mm x 15.25 M	1/4" x 59" x 50'
CFWO-40SB-3750	12 mm x 1500 mm x 15.25 M	1/2" x 59" x 50'
CFWO-40SB-5050	15 mm x 1500 mm x 15.25 M	5/8" x 59" x 50'
CFWO-40SB-7550	20 mm x 1500 mm x 15.25 M	3/4" x 59" x 50'
CFWO-40SB-1050	25 mm x 1500 mm x 15.25 M	1" x 59" x 50'

SPECIAL ORDER SPECIAL ORDER ITEMS MAY EXPERIENCE DELAYED DELIVERY TIME.

SA

Almex Fusion de Mexico
☎ 01 (477) 962 97 43

Almex Peru S.A.C.
☎ 51 999 894040

Shaw Almex Chile SpA
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada
☎ +51 31 3120 3737

ALMEX GROUP
www.almex.com 1.800.977.5423