

# FUSIONWEAR 60

**FusionWear 60** is a specially blended tough rubber compound, ideal in the handling of coarse materials where impact and abrasion wear exist.

## FEATURES:

- High resilience and resistance to permanent deformation makes FusionWear 60 the ideal product for wear problems in the handling of large particle coarse ore
- Offers excellent flexibility and enhances the movement of material fines, eliminating caking or buildup of product fines when mixed with larger particles
- Fusion Wear is manufactured with a proprietary bonding layer technology, available on one or both sides
- Exceptional wear and tear resistance
- Positive noise reduction
- Optimum performance & reliability

**SPECIAL  
ORDER**

SPECIAL ORDER ITEMS  
MAY EXPERIENCE DELAYED  
DELIVERY TIME.

## PROPERTIES:

Tensile Strength: 28.5 Mpa (2700 psi)

Elongation at Break: 500 %

Density: 1.12 g / cm<sup>3</sup>

Hardness: 60 (+/-5) Shore A

Abrasion Resistance: 105 mm<sup>3</sup>

Groove Dimensions:

4 mm x 3 mm (3/16" x 1/8")

Diamond Dimensions:

45 mm x 79 mm (1 13/16" x 3 1/8")

Photos courtesy of Cal Splice & Components Inc,  
California USA and Columbia Basin Belt & Rubber, WA, USA

PRODUCT CODE	DIMENSIONS - METRIC (TxWxL)	DIMENSIONS - IMPERIAL (TxWxL)
CFW-60SB-1250	3 mm x 1500 M x 15.25 M	1/8" x 59" x 50'
CFW-60SB-2550	6 mm x 1500 M x 15.25 M	1/4" x 59" x 50'
CFW-60SB-3750	10 mm x 1500 M x 15.25 M	3/8" x 59" x 50'
CFW-60SB-5050	12 mm x 1500 M x 15.25 M	1/2" x 59" x 50'
CFW-60SB-6250	15 mm x 1500 M x 15.25 M	5/8" x 59" x 50'
CFW-60SB-7550	20 mm x 1500 M x 15.25 M	3/4" x 59" x 50'
CFW-60SB-1050	25 mm x 1500 M x 15.25 M	1" x 59" x 50'

GL

Shaw Almex  
Mining Equip. (Tianjin) Co. Ltd.  
☎ +86 (22) 2388-9075

PT. Shaw Almex  
Indonesia  
☎ +61 488 780243

Shaw Almex  
Pacific Pty Ltd. Qld  
☎ 61 7 4774 2011

Shaw Almex  
Pacific Pty Ltd. WA  
☎ 61 8 9358 5860

Shaw Almex  
India PVT. Ltd.  
☎ 91-129-2274624

**ALMEX**  
GROUP  
www.almex.com 1.800.977.5423