

STEEL CORD BELT SPLICE KIT

Fusion provides a Steel Cord Belt splice kit, customized for your splice requirements and shipped quickly and with care, in well packed and marked crates, directly to your work site.

Steel Cords kits are custom calendared to gauge with cable bonding gum for quicker splice assembly.

Buying a custom splice kit provides the following benefits:

- Price is comparable if not lower than most competitors,
- No wasted splice materials,
- No additional handling or transportation required when shipped to your shop or work site,
- No need to store and maintain splicing material inventory,
- No need to monitor splice material expiry.
- Shelf Life of the Steel Cord Belt Splice Kit is 6 months without refrigeration (20 °C or 70 °F).

Note: Actual contents will depend on your belt specifications and splice requirements.

Kits are customized-to-order specifically to your conveyor belt specification and splice requirements.

The Steel Cord Belt Splice Kit is carefully packed and shipped directly to your work site, ready-for-use, with the details marked on the crate exterior.

Please fill out this **Steel Cord Conveyor Belt Splice Kit Questionnaire** and our experts will customize your splice kit accordingly.



Scan Me

Your Steel Cord Belt Splice Kit Typically contains:

- AA-STC Green Poly Cover Stock
- AA-STG Blue Poly Tie Gum
- AA-STN Belt Noodles
- AA-BFS Breaker Fabric
- HC1 Vulcanizing Cement
- HSP Steel Cord Primer
- HST Splice Surface Prep
- Other items: Silicone Release Paper, Cure Card, Splice ID Labels, Cement brushes, Rags

Product Code:

AA-SCSK - {Belt Width} - {Covers}

FULL KIT EXAMPLE:

AA-SKF36-3-330-187X062

DESC: steel cord splice kit for a 42" st 1250 piw belt w/ 1/4 x 1/8 steel cord covers



SPECIAL ORDER SPECIAL ORDER ITEMS MAY EXPERIENCE DELAYED DELIVERY TIME.

SA

Almex Fusion de Mexico
☎ 01 (477) 962 97 43

Almex Peru S.A.C.
☎ 51 999 894040

Shaw Almex Chile SpA
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada
☎ +51 31 3120 3737

ALMEX
GROUP
www.almex.com 1.800.977.5423