

# HPPC-100

## HIGH FLOW/CAPACITY PUMP & RESERVIOR

The HPPC-100 Pump has a 100 US Gallon reservoir and can pressurize and drain the pressure bags as well as cool the press.

Designed to be moved by forklift, this pump replaces the use of up to 5 standard pump units and can rapidly pressurize, depressurize, and cool the vulcanizing press.

### FEATURES:

- Replaces up to 5 standard pumps
- Reduces splice times with rapid pressurization and cooling functions
- Pressurizes the bags in the press and then draws the fluid from the bags back to the reservoir during depressurization.
- Pump can cool the press
- Pressure and Cooling manifolds are configured based on the vulcanizing press it is used with
- Voltage, phase and cycle as required
- Requires an independent power supply
- Built in pressure bag evacuation pump
- Storage space for cables and hoses

### OPTIONS:

- 50 or 60 Hz motor

### SPECIFICATIONS

- General Dimensions: H:737 mm x W:1168 mm x D:2032 mm (H:29" x W:46" x D:80")
- Weight, empty: 453.6 kg (1000 lbs.)
- Weight, full: 900 kg (2000 lbs.)
- Pressure Range: 7-14 kg/cm<sup>2</sup> (100-200 PSI)
- Flow Rate @ 14 bar (L/min): 64 (99)
- Reservoir Volume: 455 L (120 G), Actual: 552 L (146 G)
- Pump Power: 3.73 kW (5 HP)



GL

Shaw Almex  
Mining Equip. (Tianjin) Co. Ltd.  
☎ +86 (22) 2388-9075

PT. Shaw Almex  
Indonesia  
☎ +61 488 780243

Shaw Almex  
Pacific Pty Ltd. Qld  
☎ 61 7 4774 2011

Shaw Almex  
Pacific Pty Ltd. WA  
☎ 61 8 9358 5860

Shaw Almex  
India PVT. Ltd.  
☎ 91-129-2274624


**ALMEX**  
GROUP  
www.almex.com 1.800.977.5423