

# HPPC-500

## HYDRAULIC PRESSURE & COOLING WAGON

A field service trailered pump, designed to supply multiple vulcanizers. Pull up to your splice site with all you need to get your vulcanizer operational. Electrical power is required.

This sturdy custom-designed, dual-axle, tandem trailer includes the required electrical and hydraulic system components for the onboard 500-gallon pump.

### ■ FEATURES:

#### TRAILER

- Trailer fitted with two pump combinations capable of pumping glycol solution to pressurize and cool the vulcanizer and air compressor to purge the vulcanizer platens of water
- Sturdy custom designed dual-axle tandem trailer
- High strength diamond deck, non-skid platform finished in corrosion-resistant paint
- Trailer is capable of 14000 Lbs.
- Frame fitted with lifting lugs and leveling capabilities
- A pintel hitch and rugged 16" rubber tires
- Filling port step

#### CONTROLS

- Easy-to-use, weatherproof remote-control panel to control function of glycol/water solution for the vulcanizer
- Stop/Start switch for manual control of the pump motor
- Directional four position control valve to select pressure, platen cooling, air purge or off
- Power driven electrical reels for easy hook-up and storage of remote-control electrical cable and supply and return hoses



NA

Shaw Almex  
Europe B.V.  
☎ 31 646648648

Shaw Almex  
Industries, Canada  
☎ 1 905 643 7750

Shaw Almex  
Industries, Canada  
☎ 1 705 746 5884

Shaw Almex  
Fusion, LLC. U.S.A.  
☎ 1 404 292 8600

Shaw Almex  
Africa (Pty) Ltd.  
☎ 27 11 794 8262


**ALMEX**  
GROUP  
[www.almex.com](http://www.almex.com) 1.800.977.5423