

HPPC-500

HYDRAULIC PRESSURE & COOLING WAGON

A field service trailered pump, designed to supply multiple vulcanizers. Pull up to your splice site with all you need to get your vulcanizer operational. Electrical power is required.

This sturdy custom-designed, dual-axle, tandem trailer includes the required electrical and hydraulic system components for the onboard 500-gallon pump.

■ FEATURES:

TRAILER

- Trailer fitted with two pump combinations capable of pumping glycol solution to pressurize and cool the vulcanizer and air compressor to purge the vulcanizer platens of water
- Sturdy custom designed dual-axle tandem trailer
- High strength diamond deck, non-skid platform finished in corrosion-resistant paint
- Trailer is capable of 14000 Lbs.
- Frame fitted with lifting lugs and leveling capabilities
- A pintel hitch and rugged 16" rubber tires
- Filling port step

CONTROLS

- Easy-to-use, weatherproof remote-control panel to control function of glycol/water solution for the vulcanizer
- Stop/Start switch for manual control of the pump motor
- Directional four position control valve to select pressure, platen cooling, air purge or off
- Power driven electrical reels for easy hook-up and storage of remote-control electrical cable and supply and return hoses



GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423