

HPP20-4

The Original Almex Fluid Pressure/Cooling System for Heavyweight Belt Vulcanizers. Equipped with a fluid level gauge, pressure gauge, pressure control valve and pressure safety valve.

FEATURES:

- Welded aluminum frame construction
- Fluid (water or water/glycol) reservoir
- Rugged, reliable piston pump
- 3/4 HP motor
- Pressurize an overall platen area up to 2.5m² (4000 in²).
- Voltage, phase and cycle options to work with your vulcanizer

PRODUCT INFORMATION

- Capacity: 11.4 Liters/minute (3 US Gallons/minute)
- Tank Volume: 75 Liters (20 US Gallons)
- Weight: 125 Lbs.(57 kg) -empty
- Pressure ranges: 7-14 kg/cm² (100-200 psi)
- Large flat-free wheels for ease of transportation

OPTIONS:

- 50 or 60 Hz motor
- Valves for Water cooling (HPPC20-4)
- Ground-Fault



MODEL	DESCRIPTION
HPP20-4	75 Liter (20 US gallon) pump
HPP20-4-GF	75 Liter (20 US gallon) pump with Ground Fault circuitry
HPPC20-4	75 Liter (20 US gallon) pump with cooling option for pressurizing and cooling
HPPC20-4-GF	75 Liter (20 US gallon) pump with cooling option for pressurizing and cooling and Ground Fault circuitry
HPP RES	Additional 75 Liter (20 US gallon) capacity pump reservoir unit

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624


ALMEX
GROUP
www.almex.com 1.800.977.5423