

PUMPPACK 1200

Containment Spray application for up to 1200 TPH conveyor capacity. Chemical Injection into water spray controls dust with less moisture while recapturing material particles embedding them back into the main material flow.

FEATURES:

- Compact arrangement with Multistage Pump and Dosing Pump
- Programmable PLC Interface
- Suitable for loading/unloading hopper Containment Spray Applications
- Suitable for Inline Dust Control Applications up to 1200 TPH belt conveyor capacity
- NEMA Rated IP 55 Enclosure
- Outdoor Weatherproof Design
- Easy to operate External Controls
- For Dual Application Point Locations
- Specially designed for surfactant-based chemical applications



SPECIFICATIONS	
Capacity:	Max 20 M ³ (706.3 ft ³) with Tt Head of 60 M (196.9 ft)
Working Pressure:	Max 10 bar (145 PSI)
Power Requirements:	1 x 11 Kw/3ph/380 V
Dimensions:	1430 mm (H) X 500 mm (W) X 1100 mm (L) (56.3" x 19.7" x 43.3")
Operating Mode:	Manual and Fully automatic
Display Control:	Wientek HMI 178 mm (7") Interactive Touch Screen
Inlet Port:	Fresh water, threaded, 76.2 mm (3") diameter
Chemical Din connector:	12.7 mm (1/2") diameter
Outlet Port:	Solution mixture threaded type 76.2 mm (3") diameter

SA

Almex Fusion de Mexico
☎ 01 (477) 962 97 43

Almex Peru S.A.C.
☎ 51 999 894040

Shaw Almex Chile SpA
☎ +56 2 2 745 3969

Almex Indústria do Brasil Limitada
☎ +51 31 3120 3737


ALMEX
GROUP
www.almex.com 1.800.977.5423