

ABB SERIES

AIR BRAKE

Almex equipment has a reputation of being designed for harsh environments and Almex Belt Brakes are the most sophisticated and state of the art in the world. By the very nature of a belt brake, it must prevent catastrophic events and so only the highest quality components are used with redundant backups designed into the units.

Air brake units allow for careful and controlled descent of the belt. Units can be supplied in tandem to ensure a safer installation. The brakes are engineered with higher safety factors and manufactured to the highest level of accuracy as they are a critical component to a safe belt installation.

Belt brakes are supplied with dual pressure bags to provide redundancy during operation. The frames are welded and fabricated from high strength steel by Almex experienced welders to the highest standards. The bolts are cold rolled from high tensile steel to provide the strongest possible bolts.

Belt Brakes can be operated manually or as part of an integrated system. With the optional speed sensors, belt speed readings could be sent to the AIC² (Almex Integrated Controls) to detect "runaway" scenarios and arrest the conveyor belt by activating the Belt Clamps automatically. Wireless tablets can be added which allow for remote and safe operation of the units.

The units shown here will generate more than 200 tons of clamping force each. The Belt Brakes are manufactured to such high-quality standards that they come with a lifetime frame warranty from Almex.

The number of clamps and the configurations can be modified based upon the installation requirements for control and safety.



FEATURES:

- Belt brakes can be manual or have sensors built in to detect "run-away" scenarios and arrest the conveyor belt release
- Belt Clamps are available with a Hydraulic/spring design which will clamp shut on the conveyor belt securing it safely in the case of a run-away belt
- Wireless tablets can be added which allow for remote and safe operation of the units
- Additional Air brake units allow for careful and controlled descent of the belt and units can be supplied in tandem to ensure additional safety and redundancy
- Almex uses only drives, couplings and frame construction that exceed standards to ensure the safety of the operators and protect your infrastructure

OPTIONS:

- Speed Sensors
- Integration with AIC²
- AlmexPad Sr with application for remote operation
- Commissioning and start-up services are available

Applications for belt brakes have unique requirements based upon the length of the conveyor, the width of conveyor belt, the slope of the belt and the amount of conveyor belt being installed. Almex engineers undertake detailed finite element analysis and strain calculations to ensure that units able to withstand the loads.

Air Brakes are designed and manufactured according to the specifications required. Please contact your Sales Representative or local Almex office to discuss.

NA

Shaw Almex
Europe B.V.

☎ 31 646648648
Drachten, The Netherlands

Shaw Almex
Industries

☎ 1 905 643 7750
Stoney Creek, Ontario

Shaw Almex
Industries

☎ 1 705 746 5884
Parry Sound, Ontario

Shaw Almex
Fusion, LLC.

☎ 1 404 292 8600
Decatur, Georgia, USA

Shaw Almex
Africa (Pty) Ltd.

☎ 27 11 794 8262
South Africa



Shaw
Almex
Industries Ltd.

1.800.977.5423
www.almex.com

sales@almex.com