

Model – SOLO Xpress	Maximum operating pressure 100 PSI (7 kg/cm ²) Maximum temperature 325 deg F (160 deg C)
----------------------------	---

MODEL	PLATEN SIZE		MAXIMUM BELT WIDTH		WEIGHTS				OVERALL HEIGHT		OVERALL WIDTH		OVERALL LENGTH	
					TOP HALF		TOTAL							
	IN	MM	IN	MM	LBS	KG	LBS	KG	IN	MM	IN	MM	IN	MM

Rhomboid platens built on a 22 degree bias with a “left-hand” lead.

SOLO-1332-22-100	13 x 32	330 x 815	24	600	78	35	172	78	18	455	18	455	51	1295
SOLO-1337-22-100	13 x 37	330 x 940	32	800	85	39	185	84	18	455	18	455	56	1420
SOLO-1343-22-100	13 x 43	330 x 1090	36	900	100	45	210	95	19	480	18	455	62	1575
SOLO-1350-22-100	13 x 50	330 x 1270	42	1050	134	61	310	141	20	510	18	455	69	1750
SOLO-1353-22-100	13 x 53	330 x 1345	42	1050	150	68	340	155	21	535	18	455	72	1830
SOLO-1356-22-100	13 x 56	330 x 1420	48	1200	156	71	350	159	21	535	18	455	75	1905

Model below not available with fast heat.

SOLO-1370-22-100	13 x 70	330 x 1780	60	1500	234	106	510	231	24	610	18	455	90	2285
------------------	---------	------------	----	------	-----	-----	-----	-----	----	-----	----	-----	----	------

Specifications are approximate and subject to change without notice.

Custom Heavy Duty Frame (for continuous shop or repeated use application) available upon request. Discuss with your local vulcanizer sales representative.
All SOLO models include side carrying handles.
Optional 1/8 inch (3 mm) aluminum plate available for side by side arrangement. Available on request.