



Shaw Almex



FEATURES:

- Features a faster, IP-rated 1HP motor and quieter operation than the HPP20-4
- Significantly higher pump flow capacity, nearly double that of HPP20-4
- Supports fluid pressurizing and water cooling for press operations on the standard model
- Digital data output connection for T6L, T6GFXP and SG1 Control Boxes
- Catwalk-ready, heavy duty wheel axle with run flat tires
- Large reservoir access port on the top for servicing, and filling or draining
- Easily serviced corrosion resistant strainer
- Corrosion resistant piping and fittings
- DOL IP-66 motor starter with thermal overload protection
- Certified SS large hook capacity hoist ring
- Diaphragm style pump providing isolation between pumping fluid and pump components – improved reliability

- Easy access panels and side panel hook-ups with clear labelling and instructions
- Robust cable and hose hooks
- Enclosed/protected system components
- Certified safety relief valve

OPTIONS:

- HP25MAX-GF: Ground Fault version of the HP25MAX
- HP25MAX-RES: 94.6 litre / 25 US Gallon Reservoir Unit for additional fluid capacity

SPECIFICATIONS

- General Dimensions: H:1170 mm x W:610 mm x D:865 mm (H:46" x W:24" x D:34")
- Weight, empty: 99.8 kg (220 lbs)
- Weight, full: 194 kg (428.5lbs)





NA

Shaw Almex Europe B.V. • 31 646648648 Shaw Almex Industries, Canada **1** 905 643 7750 Shaw Almex Industries, Canada \$1 705 746 5884 Shaw Almex Fusion, LLC. U.S.A. \$1 404 292 8600 Shaw Almex Africa (Pty) Ltd. 27 11 794 8262

